

## Initial 1551E Set up for WinLEBCI and SIMM Users ONLY

**Note:** If you are *NOT* a WinLEBCI or SIMM user, please disregard this set-up sheet, and please refer to the Getting Started Guide for installation instructions.

**STEP 1:** Remove 1551E from box, attach cable to scanner and plug scanner into terminal.

**STEP 2:** Power up the computer terminal.

**STEP 3:** Scan the TWO barcodes associated with the task you are to perform; WinLEBCI requires first two barcodes, SIMM requires last two barcodes.

Reset factory defaults

Predefined terminal selections - RS-232 - standard RS-232 C (9600, 7, E, 2)

RS-232 - postamble - Carriage Return



46\42\41\4A\01\24\45\5A\3E\0D\60

Disable all symbologies

Code 11 - active

Code 11 - check digit - 1 digit (\*)

Code 11 - check digit - checked and transmitted (\*)

Code 39 - active (\*)

Code 39 - format - full ASCII

Code 128 / EAN 128 - active



41\4B\42\44\45\43\45\45\41\4C\42\4B\41\5A\60

**WinLEBCI Users:**  
Both barcodes must be scanned in the order presented before installing the scanner for the first time.

Reset factory defaults

Predefined terminal selections - Keyboard wedge - standard PC - QWERTY English

Keyboard wedge - postamble - Tab



46\42\41\4A\03\08\45\5A\04\02\08\60

Disable all symbologies

Code 11 - active

Code 11 - check digit - 1 digit (\*)

Code 11 - check digit - checked and transmitted (\*)

Code 39 - active (\*)

Code 39 - format - full ASCII

Code 128 / EAN 128 - active



41\4B\42\44\45\43\45\45\41\4C\42\4B\41\5A\60

**SIMM Users:**  
Both barcodes must be scanned in the order presented before installing the scanner for the first time.

**Note:** Scanner configuration needs only to be performed once prior to initial use. The 1551E scanner will retain configuration settings even if power is disconnected. Technicians – please retain for your records.

Part No. 071632-001



\*071632-001\*

**Intermec**  
*Technologies Corporation*

6001 36th Avenue West  
P.O. Box 4280  
Everett, WA 98203-9280

© 2001 Intermec  
All Rights Reserved